Epson EB-1930



DATASHEET



















Affordable, compact and bright projection from a feature packed device

An ideal device for corporate or educational use, the EB-1930 is a great combination of quality output and features at an affordable price.

Convenient use

The Epson EB-1930 combines high-quality output, value-added features and affordability, into a compact and portable projector. It is perfect for corporate or educational use, as it can be easily installed in meeting rooms or used portably from a desktop.

High quality picture

Utilising Epson's 3LCD technology to ensure clearly projected images, the EB-1930 produces vivid, natural colours and an equally high White and Colour Light Output, even in daylight.

Connectivity

The EB-1930 boasts a DisplayPort connector, allowing you to show high definition audio and video content with ease.

Enhanced productivity

Productivity can be greatly increased with a range of features available with the EB-1930, such as Quick Corner.

KEY FEATURES

- Ultra bright output 4,200 lumens White/Colour Light Output
- Picture quality
 3LCD technology for vivid colours
- Clock / Schedule
 Program projector actions in advance
- PC free/Slide show
 Read PDFs directly from a USB stick





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.63 inch with MLA (D7)

IMAGE

Colour Light Output 4,200 lumen-2,730 lumen (economy)
White Light Output 4,200 lumen - 2,730 lumen (economy)

Resolution XGA, 1024 x 768, 4:3

Contrast Ratio 3,000 : 1

Lamp 215 W, 3,500 h durability, 5,000 h durability (economy mode)

Keystone Correction Auto vertical: \pm 30 °, Manual horizontal \pm 30 °

Colour Processing 10 Bits

OPTICAL

Projection Ratio 1.38 - 2.24:1

Zoom Manual, Factor: 10 - 16

Projection Size 30 inches - 300 inches

Projection Distance Wide 0.8 m - 8.4 m (60 inch screen)

Projection Distance Tele 1.4 m - 13.9 m (60 inch screen)

 Projection Lens F Number
 1.51 - 1.99

 Focal Distance
 18 mm - 29 mm

 Focus
 Manual

 Offset
 8.6 : 1

CONNECTIVITY

USB Display Function 3 in 1: Image / Mouse / Sound

Interfaces USB 2.0 Type B, USB 2.0 Type A, RS-232C, HDMI in, RGB out, Stereo mini jack audio out,

RGB in (2x), Stereo mini jack audio in (2x), 10 Base-T, VGA in (2x), VGA out, Composite in,

Display Port

ADVANCED FEATURES

Security Kensington lock, Security bar, Control panel lock, Password lock

Features AV Mute Slide, Automatic input selection, Automatic keystone correction, Direct Power on/off,

Document Camera Compatible, Freeze image, Instant on/off, JPEG Viewer, Network

administration, PC Free, Quick Corner, Slide show, Split-Screen-Function

Video Colour Modes Blackboard, Dynamic, Photo, Presentation, sRGB, Theatre, Whiteboard, DICOM SIM

GENERAL

Energy Use 298 W, 212 W (economy), 0.44 W (standby)
Product dimensions 377 x 271 x 108 mm (Width x Depth x Height)

Product weight 3.7 kg

Noise Level Normal: 37 dB (A) - Economy: 29 dB (A)

Included Software EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection, EasyMP Slide

Converter

Loudspeaker 10 W

OTHER

Warranty 36 months On site service or 8,000 h, Lamp: 12 months or 1,000 h

Optional warranty extension available

Epson EB-1930

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Software (CD)
- User manual
- User manual (CD)
- Remote control incl. batteries



OPTIONAL ACCESSORIES


Epson EB-1930

- Air Filter ELPAF41
 - V13H134A41
- Lamp ELPLP74 V13H010L74
- Soft Carry Case ELPKS65 V12H001K65
- Ceiling Mount (White) ELPMB23 V12H003B23
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14

LOGISTICS INFORMATION

sku	V11H506041
EAN code	8715946517155
Dimensions Single Carton	762 x 432 x 324 mm
Carton Weight	12.9 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	40 Units
Pallet Size Block	50 Units





Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate. Web: www.epson.co.uk www.epson.ie

